


VALSTOP - EUROSTOP

Valvola di ritegno
Check valve


Art. H.0041 FOOTY



Valvola di fondo con succheruola, con otturatore a doppia guida, sabbiata.
Foot valve with strainer, with double-guide jumper, sandblasted.

SIZE	¾"	1"	1¼"	1½"	2"	2½"	3"	4"		
A mm	72	80	91	102	120	141	150	185		
B mm	9	11	13	14	16	16	16	16		
øC mm	45	51	61	68	80	102	117	146		
SW mm	34	40	50	55	69	85	95	123		
PN bar	8	8	8	8	8	6	6	6		
Peso/Weight gr.	215	280	430	590	870	1360	1741	3500		


Art. H.0141 VALSTOP



Valvola di ritegno a due femmine passaggio totale, con guarnizione in **fluoroelastomero**, sabbiata.
Check valve, female/female, full bore, with **fluoroelastomer** gasket, sandblasted.

SIZE	¼"	¾"	½"	¾"	1"	1¼"	1½"	2"	2½"	3"	4"
øA mm	28	28	34	41,5	50	60,5	73,5	89	114	137	142
B mm	46,5	46,5	50	59	67	76	90	101	127	150	133,5
øC mm	10	10	15	20	25	32	40	50	65	80	80
D mm	10	8,7	9,7	11,2	12,7	13,7	15,7	17,7	19,7	21,7	23
SW mm	21	21	26	32	39	49	56	69	86	100	124
Peso/Weight gr.	97	83	147	218	340	551	913	1414	2519	4447	4234


Art. H.0151 VALSTOP



Valvola di ritegno a due femmine passaggio totale, con guarnizione **NBR**, sabbiata.
Check valve, female/female, full bore, with **NBR** gasket, sandblasted.

SIZE	¼"	¾"	½"	¾"	1"	1¼"	1½"	2"	2½"	3"
øA mm	28	28	34	41,5	50	60,5	73,5	89	114	137
øB pass./bore	46,5	46,5	50	59	67	76	90	101	127	150
C mm	10	10	15	20	25	32	40	50	65	80
D mm	10	8,7	9,7	11,2	12,7	13,7	15,7	17,7	19,7	21,7
SW mm	21	21	26	32	39	49	56	69	86	100
Peso/Weight gr.	97	83	147	218	340	551	913	1414	2519	4447


Art. H.0153 VALSTOP



Valvola di fondo fil. femmina passaggio totale con filtro acciaio inox, sabbiata.
Foot valve, female threaded, full bore, with stainless steel filter, sandblasted.

SIZE	¾"	½"	¾"	1"	1¼"	1½"	2"	2½"	3"
øA mm	28	34	41,5	50	60,5	73,5	89	114	137
øB pass./bore	10	15	20	25	32	40	50	65	80
C mm	84	92	107	119	133	157	179	211	246
D mm	8,7	9,7	11,2	12,7	13,7	15,7	17,7	19,7	21,7
SW mm	21	26	32	39	49	56	69	86	100
Peso/Weight gr.	101	157	237	365	579	943	1459	2612	4535


Art. H.0157 VALSTOP/EUROSTOP



Filtro acciaio inox per valvola di fondo, per VALSTOP/EUROSTOP.
Stainless steel filter for foot valve, for VALSTOP/EUROSTOP.

SIZE	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
øA mm	21	26	32	40	49	55	68	85	99	121
øB mm	19	23	29	37	44	50	61	80	93	116
C mm	7	8	9	10	11	11	12	13	14	14
D mm	46,5	50	57	62	68	78	90	97	110	128
Peso/Weight gr.	6	8	14	20	29	35	52	88	116	167


Art. H.0161 EUROSTOP DISPONIBILE ANCHE IN OTTONE DZR ALSO AVAILABLE IN DZR BRASS



Valvola di ritegno a due femmine passaggio ridotto, con guarnizione **NBR**, sabbiata.
Check valve, female/female, reduced bore, with **NBR** gasket, sandblasted.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
øA mm	34	34,5	41,5	51	60	73	91	116,5	142
B mm	48	52,5	59	65	72,5	82,5	93,5	113	133,5
øC pass./bore	15	15	20	25	32	40	50	65	80
D mm	11,5	13	15	16	17	17	19	20,5	23
SW mm	25	31	38	47	55	67	84	98	124
Peso/Weight gr.	109	142	242	367	554	824	1512	2513	4183


Art. H.0163 EUROSTOP



Valvola di fondo tubolare fil. femmina con filtro in acciaio inox, sabbiata.
Foot valve, female threaded, with stainless steel filter, sandblasted.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
øA mm	34	34,5	41,5	51	60	73	91	116,5	142
øB pass./bore	15	15	20	25	32	40	50	65	80
C mm	90	100,5	111	122	139,5	160,5	177,5	209	247,5
D mm	11,5	13	15	16	17	17	19	20,5	23
SW mm	25	31	38	47	55	67	84	98	124
Peso/Weight gr.	121	160	253	404	562	876	1600	2629	4350

Art. H.0171 MONDIAL-NYLON




Valvola di ritegno a due femmine, con otturatore in nylon.
Check valve, female/female, with nylon jumper.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
øA mm	34	34,5	41,5	51	60	73	91	116,5	142
B mm	48	52,5	59	65	72,5	82,5	93,5	113	133,5
øC pass./bore	15	15	20	25	32	40	50	65	80
D mm	11,5	13	15	16	17	17	19	20,5	23
SW mm	25	31	38	47	55	67	84	98	124
Peso/Weight gr.	109	142	242	367	554	824	1512	2513	4183

VALSTOP - EUROSTOP

Valvola di ritegno
Check valve

Art. H.0173 MONDIAL•FOOTY




Valvola di fondo filetto femmina, otturatore in materiale plastico, filtro in acciaio inox integrato.

Check valve with female thread, with plastic jumper and integrated stainless steel filter.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
øA mm	15	20	25	30	35	45	68	77	100
øB pass./bore	32	39	46	56	69	84	100	110	140
C mm	80	87	95	107	124	140	-	-	-
D mm	10	10	14	15	16	18	20	23	24
SW mm	26	32	38	48	55	66	81	94	121
Peso/Weight gr.	80	144	213	257	490	666	866	1093	1729

Art. H.0191 MONDIAL•METAL




Valvola di ritegno a due femmine, con otturatore in metallo.

Check valve, female/female, with metal jumper.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"			
øA pass./bore	15	20	25	33	37	47			
B mm	47	53	63	70	88	97			
C mm	9	10	11	12	12	14			
SW mm	25	31	38	47	55	68			
PN bar	12	12	12	10	10	10			
Peso/Weight gr.	142	200	343	425	760	1000			

Art. H.0200 CLAPET




Valvola di ritegno a clapet orizzontale sede metallica, tipo a battente, sabbiata.

Horizontal swing check valve, with metal seat, sandblasted.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
øA pass./bore	15	20	25	33	37	47	55	70	90
B mm	47	53	63	70	88	97	120	135	180
C mm	9	10	11	12	12	14	17	17	23
SW mm	25	31	38	47	55	68	82	98	128
PN bar	12	12	12	10	10	10	8	8	8
Peso/Weight gr.	142	200	343	425	760	1000	1650	2300	5100

Art. H.0202 CLAPET



Valvola di ritegno a clapet orizzontale sede in gomma, tipo a battente, sabbiata.

Horizontal swing check valve, with NBR seat, sandblasted.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
øA pass./bore	15	20	25	33	37	47	55	70	90
B mm	47	53	63	70	88	97	120	135	180
C mm	9	10	11	12	12	14	17	17	23
SW mm	25	31	38	47	55	68	82	98	128
PN bar	12	12	12	10	10	10	8	8	8
Peso/Weight gr.	142	200	343	425	760	1000	1650	2300	5100